



*Terms & Conditions Apply (5 YEAR/3000 HOURS)

5660

Engine Type	SNK 3100-FLT, Turbo - Intercooler
Max Engine Power	58 hp (44 kw)
Rated Engine Speed (rpm)	2100
Cylinders	3
Displacement	2780 cc
Fuel Tank Capacity	55 L
Number of Gears	8 F + 8 R
Tractor min and max speed	2,35 km/h - 31 km/h
Clutch Type	Dry, double, mechanically controlled / 11" (280mm) / cerametallic
Front Axle / 4WD	Limited slip differential planet gear system, mechanical
Steering Type	Hydrostatic power
Steering Pump Output	21,8 l/min
Standard Tyres (Front)	240 / 70 R16
Standard Tyres (Rear)	13.6 - 24
ROPS	Standard
Cab with A/C	N/A
Total Weight (kg)	2680 kg
Brake Type	Oil immersed brakes (OIB) brakes foot operated, independently with provision of interlock , Hand brake

Transmission Type	Carraro T50 / 8 forward/ 8 reverse
Max Lift Capacity (Lower Link)	2200 kg
Hydraulic Pump Output	21,8 l/min
Steering Pump Output	21,8 l/min
Three-Point Linkage	Cat II, fixed lower link
Auxiliary Remote Valves	1-spool standard
Max PTO Power	48 hp
PTO Speeds (rpm)	540 / 540 E rpm
Hydraulic System	Mechanical / Category 2 compatible with position and draw control
PTO Type	Independent , Synchronized , and Synchronized PTO 35 mm - 6 tooth
Overall Length (mm)	3475 mm
Overall Width (mm)	1480 mm
Overall Height (mm)	2170 mm
Ground Clearance (mm)	245 mm
Wheelbase (mm)	2045 mm
Turning Radius with Brakes (mm)	3000 mm
Turning Radius without Brakes (mm)	3400 mm

