



\*Terms & Conditions Apply (5 YEAR/3000 HOURS)

## 7590 4WD

Engine Type	4-cylinder, direct injection diesel, intercooled turbocharged
Max Engine Power	92 hp (69 kw)
Rated Engine Speed (rpm)	2300
Cylinders	4
Displacement	3533 cc
Fuel Tank Capacity	70 L
Transmission Type	12F + 12R Forward-Reverse Synchro-Shuttle with speed synchromesh & constant mesh
Hydraulic System	Open-centre full-live, position & draft control, dual spool auxiliary
Max Lift Capacity (Lower Link)	2500 kg
Hydraulic Pump Output	55,6 l/min
Steering Pump Output	17,4 l/min
Auxiliary Remote Valves	2-spool standard
Overall Length (mm)	4115,8 mm
Overall Width (mm)	1963,4 mm
Overall Height (mm)	2530 mm
Turning Radius with Brakes (mm)	3990 mm
ROPS	Standard
Cab with A/C	Optional

Front Axle / 4WD	Mechanical engagement, limited slip differential
Number of Gears	12 F + 12 R
Tractor min and max speed	2,8 km/h - 33,8 km/h
Clutch Type	Dual dry, cerametallic lining, 12 inch
Steering Type	Hydrostatic power
Steering Pump Output	17,4 l/min
Brake Type	Oil immersed brakes (OIB) brakes foot operated, independently with provision of interlock, Hand brake
Three-Point Linkage	Cat II telescopic lower link with stabilizers
PTO Type	Independent single lever engagement
Max PTO Power	75 hp
PTO Speeds (rpm)	540 / 1000
Ground Clearance (mm)	350 mm
Wheelbase (mm)	2179 mm
Standard Tyres (Front)	12.4 x 24
Standard Tyres (Rear)	18.4 x 30
Turning Radius without Brakes (mm)	4570 mm
Total Weight (kg)	3618 kg

