



*Terms & Conditions Apply (5 YEAR/3000 HOURS)

6675



Specification	6675 (Cab / Rops)
Engine Type	4-cylinder Perkins 1104D-44T
Max Engine Power	75 hp (56kw)
Rated Engine Speed (rpm)	2200rpm
Cylinders	4
Displacement	4400 cc
Fuel Tank Capacity	70 L
Transmission Type	Type: ZF T-537 / Gears: 16 Forward / 8 Reverse
Number of Gears	16 F + R 8
Front Axle / 4WD	Limited slip differential planet gear system, mechanical
ROPS	Standard
Cab with A/C	Optional
Tractor min and max speed	2,35 km/h - 34,6 km/h
Turning Radius with Brakes (mm)	3500 mm
Ground Clearance (mm)	285 mm
Wheelbase (mm)	2130 mm
Standard Tyres (Front)	260 / 70 R18 (Std) / 280 / 70 R20 (Opt)
Standard Tyres (Rear)	380 / 70 R24 (Std) / 380 / 70 R28 (Opt)
Brake Type	Oil immersed brakes (OIB) brakes foot operated, independently with provision of interlock, Hand brake

Max Lift Capacity (Lower Link)	2800 kg
Hydraulic Pump Output	48,5 l/min
Steering Pump Output	19,8 l/min
Three-Point Linkage	Cat II, fixed lower link
Auxiliary Remote Valves	2-spool standard
PTO Type	Independent, Synchronized, and Synchronized PTO 35 mm - 6 tooth
Max PTO Power	65 hp
PTO Speeds (rpm)	540 / 540 E rpm
Hydraulic System	Mechanical / Category 2 compatible with position and draw control
Clutch Type	Dry, double, mechanically controlled / 11" (280mm) / cerametallic
Steering Type	Hydrostatic power
Steering Pump Output	19,8 l/min
Overall Length (mm)	4020 mm
Overall Width (mm)	1680 mm
Overall Height (mm)	Rops 3180 mm / Cab 2130 mm
Total Weight (kg)	2750 kg / 3180 kg
Turning Radius without Brakes (mm)	3800 mm

