



*Terms & Conditions Apply (5 YEAR/3000 HOURS)

6060 2WD

Engine Type	4-cylinder, 4-stroke, water-cooled, direct injection diesel
Max Engine Power	60 hp (45 kw)
Rated Engine Speed (rpm)	2100
Cylinders	4
Displacement	3533 cc
Fuel Tank Capacity	60 L
Transmission Type	Partial Synchromesh
Number of Gears	15 F + 3 R
Tractor min and max speed	1,63 km/h - 31,69 km/h
Clutch Type	Dry dual, mechanically controlled / 12 inch
Front Axle / 4WD	3-Piece Adjustable Front axle
Steering Type	Hydrostatic power
Steering Pump Output	17,5 l/min
Turning Radius with Brakes (mm)	3250 mm
Turning Radius without Brakes (mm)	3600 mm
ROPS	Standard
Cab with A/C	N/A
Brake Type	Oil immersed brakes (OIB) brakes foot operated, independently with provision of interlock, Hand brake

Hydraulic System	Full-live with position & draft control, dual spool auxiliary
Max Lift Capacity (Lower Link)	2200 kg
Hydraulic Pump Output	57,5 lpm
Steering Pump Output	17,5 lpm
Three-Point Linkage	Cat II, fixed lower link
Auxiliary Remote Valves	2-spool standard
PTO Type	Rear single lever independent
Max PTO Power	49 hp
PTO Speeds (rpm)	540 / 540E
Overall Length (mm)	4052 mm
Overall Width (mm)	1960 mm
Overall Height (mm)	2670 mm
Ground Clearance (mm)	350 mm
Wheelbase (mm)	2150 mm
Standard Tyres (Front)	7.5 x 16
Standard Tyres (Rear)	16.9 x 28
Total Weight (kg)	3100 kg

