



DEUTZ-FAHRAGROLUX 90 DT E2 30"

*South African standard specifications 2024

Powertrain standard sealing
Telescopic steering column
Adjustable seat(PVC)(Mechanical suspension)
Safety seat belt
Analogue display
Rear mudguards
Front headlights for left hand traffic
Foldable 2 post rear safety frame
Rear telescopic mirror
Sun roof canopy
Toolbox

*South African standard specifications 2024

1) The above configuration is intended as general information.

2) The right to make modifications is reserved. Please always consult your DEUTZ-FAHR authorised importer as the sole source of current information on our vehicles technical features.

3) All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

Machine equipment

Engine

4 Cylinder turbo engine with 4000cm capacity	Standard
Max. power CE(2000/25): 87hp/64,4kw	Standard
Liquid/oil cooled engine	Standard
Dry air filter	Standard
Mechanical engine governor	Standard
8" lair filter with dust ejector	Standard
Vertical exhaust pipe	Standard
Battery: 12V - 100AH - 1000A(EN)/650A(IEC)/560A(DIN)	Standard
Without air cleaner extension	Standard

Transmission

Synchro gearbox	Standard
Transmission oil cooler	Standard
Transmission 40km/h	Standard
5 Speed gearbox 20F + 20R with creeper	Standard

PTO

Hydraulically controlled PTO	Standard
Fixed PTO shaft	Standard
Without ground speed PTO	Standard
Hydraulic multi-disc oil immersed PTO clutch	Standard
Rear PTO: 540 - 1000	Standard

Axles and brakes

Rear differential lock	Standard
Fully hydrostatic independent braking on 4 wheels with oil immersed disc brakes	Standard
Without seperate brake valve	Standard
Without trailer brakes	Standard

*South African standard specifications 2024

1) The above configuration is intended as general information.

2) The right to make modifications is reserved. Please always consult your DEUTZ-FAHR authorised importer as the sole source of current information on our vehicles technical features.

3) All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

Steering

Hydrostatic steering	Standard
----------------------	----------

Hitch + lift

Mechanically operated hydraulic rear lift	Standard
Lever controls to driver right hand side	Standard
Open center hydraulic system with constant pump (56ltr/min)	Standard
3 Point linkage Cat 2 with fixed upper and lower links	Standard
Telescopic stabilizers	Standard
Mechanical rear lift	Standard
Lifting arms with float position	Standard
2 Rear distributors with quick couplers	Standard
Swinging drawbar Cat "A"	Standard

Tyres

380/85 R24 (14.9 R24) Front	Standard
460/85 R30 (18.4 R30) Rear	Standard
Tyre brand supplied by the factory	Standard

Ballast

Front weight frame (20kg) with hitch + front weights (320kg). Total 340kg.	Standard
Ballast for the rear wheels (2x2 Total 172kg)	Standard

*South African standard specifications 2024

1) The above configuration is intended as general information.

2) The right to make modifications is reserved. Please always consult your DEUTZ-FAHR authorised importer as the sole source of current information on our vehicles technical features.

3) All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.